

WELCOME



www.swissphone.com

Swissphone Products (1/2)

- Pager & Accessories
 - Digital POCSAG receivers: Alpha / Voice with options







Analog receivers: 5-Tone, 2-Tone



 Accessories: Various charges and devices, Holster, clip, security chain etc.





DV500

Highlights

 On air text messages are to be processed and spoken out

User may define a lexicon

Ergonomic design, very rugged

One hand operation

Low battery alarm (audible and visual)

Fire at 123 Elm Street. Callers name – Jim Smith. Phone 555-1212...

Street. Callers name – Jim Smith.

Phone 555-1212



HURRICANE volce



DE920Highlights I

- 32 Cap Codes
- IP 52 protection class
- 3-line backlit LC-Display with large character set
- 9 alerts/user profiles plus 1 expansion
- One hand operation



DE920Highlights II


Option: IDEA® 128 bit encrypting

Option: ATEX

PLL technology

 Windows based programming SW









Digital Pager Accessories

- (Multi) Chargers
- Programming kits
- · Security chain, clip
- Leather bags



















Frequency spectrum and US-Approvals

Status: Okt 2004

Wavelength	VHF							UHF						
Frequency range	4m			2m				70 cm						
Frequency band	UB	MB	ОВ	UUB	UB	MB	ОВ	В	С	D	Е	F	G	Н
Frequency [MHz]	68-74	74-81	81-88	138-146	146-155	155-164	164-174	400-410	410-420	420-430	430-440	440-450	450-460	460-470
POCSAG:														
DE900 (12.5 kHz)				A (VA)	D	D	D	D	D					
DE900 (20/25 kHz)				A (FCC)										
DE516C (12.5 kHz) DE516C (20/25 kHz)				A (FCC)	A (FCC)	A (FCC)	A (FCC)				A (FCC)	A (FCC)	A (FCC)	A (FCC)
DV500 (12.5 kHz) TEXT to Voice				D(VA)	D(VA)	D(VA)	D(VA)							
DV500 (20/25 kHz)				D	A (FCC)	A (FCC)	A (FCC)				A (FCC)	A (FCC)	A (FCC)	A (FCC)
<u>5-TONE:</u>														
RE429NT+ (12.5 kHz)					Α	Α	Α			At	At	At	At	At
RE429NT+ (20/25 kHz)	y.				Α	Α	Α			Α	Α	Α	Α	Α
2-TONE:														
RE529NT+ (12.5 kHz)					Α	Α	Α							
RE529NT+ (20/25 kHz)					Α	Α	Α							

A: available (in brackets: Date of release) At: available, restricted temperature range

A (va): VA certified

A (FCC): FCC certified only

Not available

D: Feasible, (Sample available in 1 month, typ appoval 4 months)

Dt: Feasible, restricted temperature range





Swissphone Products (2/2)

System solutions, alarming systems

Satellite network components for C&C and alerting communication

- Terrestrial network components
- On-Site Solutions
- Network & Services
 - Paging Services
- Command and Control Systems







I-SEARCH What is I-SEARCH

- A local paging system, connected to the Ethernet of a company
- UHF transmitter, 4 W output or according to regulations in the country
- Web-browser based GUI (<u>Graphical User Interface</u>)
- Supports the POCSAG protocol
- Modular design, supports the interface with PABX, GSM module for SMS


I-SEARCHKey features

- Point to multipoint broadcasting
- No subscriber fee (in contrast to GSM!)
- Sends text messages
- Up to 300 individual subscribers
- Operating in a intrinsic safe environment (Ex)
- Encryption on request (IDEA 128 bit)
- Moderate one-time investment
- Marginal cost for the installation
- Open POCSAG standard (no proprietary protocol)



I-SEARCH Reference

 Training Center Boldern, Männedorf CH <u>Replacement</u> of Philips Paging System



Separate building w/ 1 floor

Separate building w/ 1 floor



We look forward to serving you